



**1 FOUNDATION PLAN**  
**SCALE 1/8"=1'-0"**



Xref P:\Projects\2005\VS567 Cour

- PLAN NOTES**
1. SLAB-ON-GRADE IS 4" THICK W/ ONE LAYER OF 6#-W14M14 W.W.F. ON 4" CRUSHED STONE OR SAND ON 10 MIL VAPOR BARRIER, UNLESS NOTED OTHERWISE.
  2. CONTROL JOINTS RECD. @ 15'-0" MIN. EA. DIRECTION. (SEE DETAIL 3/SS.01)
  3. 12" CMU BLOCK W/ #4 VERT. @ 48" o.c. (SEE 5/SS.02)
  4. REFER TO ARCH FOR ANY SLOPE, RECESS OR DRAIN IN SLAB. (MAINTAIN 4" THICKNESS)
  5. ALL FOOTING SHALL BEAR ON TAN LIMESTONE ACCORDING TO SOILS ENG. SEE GENERAL NOTES: FOUNDATION NOTE 2

**PLAN INDICATION LEGEND**

MARK	INDICATION DESCRIPTION
49	INDICATES FOOTING STEP (SEE 12/SS.01)
(F-X)	INDICATES FOOTING MARK. SEE FOOTING SCHEDULE ON SHEET SS.01 FOR FOOTING SIZE & REINFORCEMENT.
W-F-X	INDICATES WALL FIG. MARK. SEE WALL FIG. SCHED. ON SHEET SS.01 FOR WALL FOOTING SIZE & REINFORCEMENT.
(-X'-X")	INDICATES TOP OF FOOTING DEPTH. T.O.F. TO BE -1'-0" (UNO.)
[Hatched Box]	INDICATES LOAD BRNG. METAL STUD WALL (SEE SCHED.)
[Cross-hatched Box]	INDICATES LOAD BRNG. CMU STEM WALL (SEE NOTE 3)
[Diagonal Hatched Box]	INDICATES 8" 10F WALL

ISSUED FOR PROGRESS SET ONLY, NOT FOR CONSTRUCTION

**REVISIONS**

REV-11	27/27/2777

**DATE:** 01/30/2008  
**JOB NO.:** 05267  
**DRAWN BY:** DMW  
**CHECKED BY:** SH

**SHEET NO.:**  
**S2.01**

INTECH DESIGNS (INDIA)

